

(12) UK Patent Application (19) GB (11) 2 178 899 A

(43) Date of printing by UK Office 18 Feb 1987

(21) Application No 8616806

(22) Date of filing 3 Dec 1984

(86) International application data
PCT/SU84/00069 Su 3 Dec 1984

(87) International publication data
WO86/03617 Su 19 Jun 1986

(51) INT CL⁴ (as given by ISA)
H01H 13/26

(52) Domestic classification (Edition I)
H1N 542 54X 631 634 639 63X 700 701 704 854 NR PE

(56) Documents cited by ISA
US 4348563 US 3996435
US 4169971 US 3838237

(58) Field of search by ISA
INT CL⁴ H01H 13/20-26

(71) Applicant
Vsesojuzny Nauchno-Issledovatel'sky Proektno-
Konstruktorsky i Tekhnologicheskyy Institut
Vzryvozaschishennogo i Rudnichnogo Elektroobor-
udovaniya

(Incorporated in USSR),


ulitsa 50-oi Gvardeis-koj divizii, 17 Donetsk, Union of
Soviet Socialist Republics

(72) Inventors
Vyacheslav Georgievich Mironenko,
Alexandr Pavlovich Poltorak,
Vitaly Ivanovich Schutsky,
Vladimir Alexandrovich Kosovtsev,
Fedor Petrovich Chaly,
Vladislav Fedorovich Zagubeljuk,
Nikolai Ivanovich Filatov

(74) Agent and/or Address for Service
A. A. Thornton & Co., Northumberland House, 303/306
High Holborn, London WC1V 7LE

(54) Microswitch

(57) A microswitch comprises a base (1), immovable contacts (2, 3) fixed on the base (1) and an actuating lever (4) connected with the base (1) in a manner providing for its angular turn. A contact lever (6) is connected with the actuating lever (4) in a manner providing for its angular turn as well. A movable contact (9) is fixed on the free end of the contact lever (6). The microswitch is also provided with a movable contact switching mechanism made of a spring (11) and an intermediate lever (12) the ends of which are connected to each other and to the end of the contact lever (6) on which the movable contact (9) is fixed. The other end (15) of one of the elements (11, 12) of the movable contact switching mechanism is connected to the contact lever (6) whereas the other end (17) of the other element (11) is fixed on the base (1) in the area between the vertical planes passing through the point (18) of connection of the other end (15) of one of the elements (11, 12) with the contact lever (6) and through the movable contact (9).



GB 2 178 899